



**CS2674AX Ultra-high Voltage Withstanding Tester**

Dimensions: 440mm x 220mm x 340mm  
Weight(Approx): 28kg



**CS2674BX/74CX Ultra-high Voltage Withstanding Tester**

Serial products: CS2674BX、CS2674CX Dimensions: 375mm x 190mm x 280mm Weight(Approx.): 11kg



Withstanding Voltage Tester  
CS2674-10、CS2674-20、CS2674-75、CS2674-100

**Ultra-high Voltage Withstanding Tester**

Serial products:  
CS2674-10 CS2674-20  
CS2674-75 CS2674-100  
Dimensions: 600mm x 1100mm x 730mm

**Product performance**

- Split structure ensures safety while testing
- Leakage current real-time detection
- Alarm value can be preset freely
- Test time, leakage current and voltage can be displayed simultaneously
- Audible and visual alarm with disqualification
- High-voltage breakdown protection

**Customized products**

**Specifications**

Model	Output Voltage	Output Current	Test Time	Transformer	Accuracy
CS2674AX	(0 - 20)kV(AC/DC)	(0 ~ 10)mA(AC/DC)	(1 ~ 99)s	200VA	± (5%+3counts)
CS2674BX	(0 - 30)kV(AC/DC)	(0 ~ 20/10)mA(AC/DC)	(1 ~ 99)s	600VA	± (5%+3counts)
CS2674CX	(0 - 50)kV(AC/DC)	(0 ~ 20/10)mA(AC/DC)	(1 ~ 99)s	1000VA	± (5%+3counts)
CS2674-10	(0 - 10)kV(AC/DC)	(0 ~ 500/250)mA(AC/DC)	(1 ~ 99)s	5000VA	± (5%+3counts)
CS2674-20	(0 - 20)kV(AC/DC)	(0 ~ 200/100)mA(AC/DC)	(1 ~ 99)s	4000VA	± (5%+3counts)
CS2674-75	(0 - 75)kV(AC/DC)	(0 ~ 100/500)mA(AC/DC)	(1 ~ 99)s	7500VA	± (5%+3counts)
CS2674-100	(0 - 100)kV(AC/DC)	(0 ~ 100/500)mA(AC/DC)	(1 ~ 99)s	10000VA	± (5%+3counts)