

# UNITEST TELARIS® FI/RCD

## Key Functions

- Swift and easy test of RCDs (also time delayed types)

## General Information

- Designed to meet the requirements of a broad number of users including electrical contractors, property owners, building firms and industry
- Integrated socket test with contact electrode to enable the user to quickly establish incorrectly installed sockets and/or protective conductor failures
- Pre-selection of max. admissible contact voltage
- Includes a clear, large LCD display for quick pass / fail confirmation
- Auto power off

## Technical data

Display	LCD
Nominal test current	10, 30, 100, 300, 500 mA, 1A time delayed: 100, 300, 500 mA
Tolerance	+0% / -10%
Test pulse	< 300 ms
Contact voltage	25 / 50 V selectable
Mains voltage	230 V +10% / -15%
Protection class	II (double insulated)
Safety complying with	IEC61010/EN61010/ DIN VDE 0411 IEC61557/EN61557/ DIN VDE 0413
Measurement category	CAT III / 300 V
Pollution degree	2
Protection degree	IP 50
Power supply	1 x 9 V IEC 6LR61
Auto-Power-Off	
Dimensions	235 x 105 x 70 mm
Weight	approx. 700 g



## Scope of Supply:

- 1 pc UNITEST TELARIS FI/RCD
- 1 pc Protective Holster
- 1 pc Carrying Case
- 1 pc Battery 9 V, IEC 6LR61
- 1 pc Instruction Manual



## Accessories:



- |   |               |
|---|---------------|
| Professional carrying case                | Cat. No. 1229 |
| Three-Phase Adapter<br>CEE 16 A to Schuko | Cat. No. 1230 |
| Three-Phase Adapter<br>CEE 32 A to Schuko | Cat. No. 1231 |

## Order Information:

Description	Cat. No.
UNITEST TELARIS FI/RCD	<b>8968</b>
Professional carrying case	<b>1229</b>
Three-Phase Adapter 16 A	<b>1230</b>
Three-Phase Adapter 32 A	<b>1231</b>