

RH9A SERIES

HIGH RESISTANCE, HIGH VOLTAGE DECADE RESISTANCE BOX WITH SP1 SWITCH

Designed using the Cropico high quality SP1 switch combined with specially selected resistors, this range of high ohm resistance decades is ideal for the calibration of insulation test sets having a voltage rating up to 5kV. Housed in a rugged carrying case and available in either 3, 6, or 9 decades the RH9A series covers the range 1 kilo ohm to 1 tera ohm and is equally at home in the laboratory workshop or field application. A single decade unit is also available with 10 switched values from 1 kilo ohm to 1 tera ohm. Supplied complete with high voltage test leads 1 metre in length and calibration certificate.

KEY FEATURE

1, 3, 6 & 9 decades available

Range 1 kilo ohm to 1 tera ohm

Max Voltage 5kV

Accuracy $\pm 0.1\%$

Portable case

RH9A



RH9A SPECIFICATIONS

RH9A-1	RH9A-2	RH9A-3	RH9A-4	Decade	Accuracy @ Certified Voltage 1Kv Max	Typical Voltage Coeff	Max V/Step	Power Rating	Temp Coeff
	■		■	10 x 1kΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
	■		■	10 x 10 Ω	±0.1%	-	500V	1 watt	±50 ppm /°C
	■		■	10 x 100kΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
	■	■	■	10 x 1MΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
	■	■	■	10 x 10MΩ	±1%	1ppm/V	4,000V	1.5 watt	±100 ppm /°C
	■	■	■	10 x 100MΩ	±1%	1ppm/V	4,000V	1.5 watt	±100 ppm /°C
■		■	■	10 x 1GΩ	±1%	1ppm/V	5,000V	3.5 watt	±100 ppm /°C
■		■	■	10 x 10GΩ	±1%	1ppm/V	5,000V	3.5 watt	±100 ppm /°C
■		■	■	10 x 100GΩ	±2%	1ppm/V	5,000V	1.3 watt	±2,000 ppm /°C

RH9A-5 SPECIFICATIONS

Value	Accuracy @ Certified Voltage 1Kv Max	Typical Voltage Coeff	Max V/Step	Power Rating	Temp Coeff
1kΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
10kΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
100kΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
1MΩ	±0.1%	-	500V	1 watt	±50 ppm /°C
10MΩ	±1%	1ppm/V	4,000V	1.5 watt	±100 ppm /°C
100MΩ	±1%	1ppm/V	4,000V	1.5 watt	±100 ppm /°C
1GΩ	±1%	1ppm/V	5,000V	3.5 watt	±100 ppm /°C
10GΩ	±1%	1ppm/V	5,000V	3.5 watt	±100 ppm /°C
100GΩ	±2%	1ppm/V	5,000V	1.3 watt	±2000 ppm /°C
1TΩ	±2%	1ppm/V	5,000V	1.3 watt	±2000 ppm /°C

Weight

RH9A 8.8kg
 RH9A-1 7kg
 RH9A-2 8kg
 RH9A-3 8kg
 RH9A-5 0.8kg

Size

RH9A 460mm x 380mm x 160mm (W H D) approx
 RH9A-1 460mm x 380mm x 160mm (W H D) approx
 RH9A-2 460mm x 380mm x 160mm (W H D) approx
 RH9A-3 460mm x 380mm x 160mm (W H D) approx
 RH9A-5 220mm x 110mm x 90mm (W H D) approx



C/ IKEA, 51 - LOCAL B - 48940 LEIOA - VIZCAYA

TFNO.: 944803040 - FAX: 944348191

Email: isotest@isotest.es

<http://www.isotest.es>